



CK REG NUM: 2017/340833/07

VAT Num: 4580287672

243 Masjien Str, UNIT D1 Strijdom Industrial Park, STRIJDOM PARK RANDBURG 2169

Tel: 011 202 5143/ 082 700 2173/011 568 9578

Email: sales@pvcfloortile.co.za

DATA SHEET

PVCOCITY SEALER GLAZE FLOOR SEALANT

POLYMER BASED FLOOR SEALANT

Pvcocity Sealer is a liquid polymer-based floor sealant, commonly used in the industrial and domestic markets. It is formulated to use as a sealant coating that will give your floors protection against liquid spills, stains, and scuffmarks. Provides a durable coating that will extend the life of your floor.

APPLICATIONS

Pvcocity Sealer is a non-slip coating that can be applied to seal most hard floor surfaces including wood, vinyl and novilon. Pvcocity Sealer will protect and enhance the look of the floor surface as well as restore old faded surfaces. Provides a durable coating that will extend the life of your floor.

METHOD OF USE

Remove old acrylic floor polish using any Floor Stripper. Rinse and wash the surface using Pvcocity Cleaner. Ensure all detergent is removed and allow the surface to dry. Apply Pvcocity Sealer as supplied to a clean dry floor using a lambswool applicator, soft lint free or microfibre cloth. Apply evenly and thinly over the entire surface and allow 30 minutes for complete product cure. It is recommended that a minimum of 3 coats are applied. Buffing of the floor is possible 48 hours after application. Not recommended to be used on outside areas in direct sunlight.

The recommendations contained herein are based on laboratory test and in-field use experience, and are to the best of our knowledge, accurate. Since conditions of actual use are beyond our control, all recommendations are made without warranty, express or implied.

FIRST AID MEASURES

INGESTION: Administer 250ml of water to dilute stomach contents. Do not induce vomiting.

INHALATION: None

SKIN: Rinse with water and neutral detergent.

EYES: Rinse with lukewarm water