



PVCOACITY LIQUID FLOOR POLISH

POLYMER BASED FLOOR POLISH

Pvcocity Polish is a liquid polymer-based floor polish, commonly used in the industrial and domestic markets. It is formulated to use as a polish that will give your floors protection against liquid spills, stains, and scuffmarks. Regular use provides a durable coating that will extend the life of your floor.

APPLICATIONS

Pvcocity Polish is a non-slip coating that can be applied to maintain sealed wood, vinyl and novilon flooring. It is recommended to use Pvcocity Sealer Mirror Glaze Floor Sealant as the base. Apply Pvcocity Polish to a clean dry floor using a lambswool applicator, soft lint free or microfibre cloth. Allow adequate time to dry thoroughly before buffing with a hand buffer or buffing machine using a red or white buffing pad.

METHOD OF USE

Apply Pvcocity Polish as supplied to a clean dry floor using a lambswool applicator, soft lint free or microfibre cloth. Apply evenly and thinly over the entire surface and allow 30 minutes for complete product cure. Buffing the floor will increase the shine and aid in removing unwanted scuff and heel marks. Not recommended to be used on outside areas in direct sunlight.

The recommendations contained herein are based on laboratory test and in-field use experience, and are to the best of our knowledge, accurate. Since conditions of actual use are beyond our control, all recommendations are made without warranty, express or implied.

FIRST AID MEASURES

INGESTION	: Administer 250ml of water to dilute stomach contents. Do not induce vomiting.
INHALATION	: None
SKIN	: Rinse with water and neutral detergent.
EYES	: Rinse with lukewarm wate