

PVCOCITY SEALER GLAZE FLOOR SEALANT

POLYMER BASED FLOOR SEALANT

Pvcocity Sealer is a liquid polymer-based floor sealant, commonly used in the industrial and domestic markets. It is formulated for use as a sealant coating that gives floors protection against liquid spills, stains and scuffmarks. It provides a durable coating that helps extend the life of the floor.



Spill & stain protection



Non-slip coating



Restores faded surfaces



Durable coating



Hard floor use



Enhances appearance

AT A GLANCE



PRODUCT TYPE
Liquid polymer sealant



SURFACE USE
Wood, vinyl, novilon



RECOMMENDED COATS
Minimum 3



CURE TIME
30 minutes



BUFFING
After 48 hours



USE AREA
Indoor hard floors

APPLICATIONS

Pvcocity Sealer is a non-slip coating that can be applied to seal most hard floor surfaces including wood, vinyl and novilon. Pvcocity Sealer will protect and enhance the look of the floor surface as well as restore old faded surfaces. Provides a durable coating that will extend the life of your floor.

METHOD OF USE

- 1 Remove old acrylic floor polish using any floor stripper.
- 2 Rinse and wash the surface using Pvcocity Cleaner.
- 3 Ensure all detergent is removed and allow the surface to dry.
- 4 Apply Pvcocity Sealer as supplied to a clean dry floor using a lambswool applicator, soft lint free or microfibre cloth.
- 5 Apply evenly and thinly over the entire surface.
- 6 Allow 30 minutes for complete product cure.
- 7 A minimum of 3 coats is recommended.
- 8 Buffing of the floor is possible 48 hours after application.
- 9 Not recommended for outside areas in direct sunlight.

FIRST AID MEASURES

-  **INGESTION:** Administer 250 ml of water to dilute stomach contents. Do not induce vomiting.
-  **INHALATION:** None.
-  **SKIN:** Rinse with water and neutral detergent.
-  **EYES:** Rinse with lukewarm water.

The recommendations contained herein are based on laboratory test and in-field use experience, and are to the best of our knowledge, accurate. Since conditions of actual use are beyond our control, all recommendations are made without warranty, express or implied.



011 202 5143
082 534 3320



sales@pvcfloortile.co.za



www.pvcfloortile.co.za